

DECK

Built to be tough and reliable. Aluminum and Steel construction. 12,000 lb. structural capacity.



WINCH

Up to 12,000 lb. capacity winches for maximum pulling power.

BODY

Low profile and versatile. Various grid options available. 3,500 lb. lift capacity.

SPECIFICATIONS

OVERCOME THE TOUGHEST LOADING CHALLENGES

The 6 Ton XLP offers the lowest load angle in its class, for clearance on even the lowest profile vehicles. It features our exclusive No-Lube™ technology for less time on upkeep and more time on the road.

CARRIER DECK	
Capacity	12,000 lbs.
Deck Width	96 in., 102 in.
Deck Length	19 ft., 20 ft., 21 ft., 22 ft.
Material Type	Steel or Aluminum
WHEEL LIFT	
Lift Capacity	3,500 lbs.
Tow Capacity	10,000 lbs.
Maximum Extended Reach from End of Bed	68 in.
WINCH	
Winch Capacity	Single 8,000 lbs. 10,000 lbs. or 12,000 lbs.
CHASSIS	
Minimum GVWR (w/o wheel lift)	15,000 lbs.
Minimum GVWR (w/ wheel lift)	19,500 lbs.
Cab to Axle (CA) Range	120 in. (19 ft. deck) 120 in.-132 in. (20 ft. deck) 132 in.-144 in. (21 ft. deck) 144 in.-156 in. (22 ft. deck)

BECAUSE THE
WORK **DEMANDS** IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

LIGHT DUTY CARRIER

6 TON XLP

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 functions)		•
DECK & SUBFRAME		
STEEL		
Single Sheet 3/16 in. Diamond or Smooth Decking	•	
5 in. Removable Tubular Steel Rails		•
5 in. Polished Aluminum Blade Rails		•
ALUMINUM		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5 in. Removeable Blade Rails (NGAR)		•
5 in. Fixed Blade Rails (NGAF)		•
STEEL & ALUMINUM		
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Headboard - Deck Mounted or Stationary Frame Mounted	•	
Side Recovery System (SRS)		•
Galvanized Subframe & Wheel Lift		•
Dual Angle Deck		•
102 in. Deck Width		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Greaseable Pivot Joints		•
Wheel Lift Grids (Manual, Pivoting or Hydraulic)		•
Camlocks ILO of T-Handle (Manual or Pivoting Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual or Pivoting Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available)		•
*Option available when wheel lift is deleted		
ACCESSORIES		
Toolbox (36 in., 48 in. or 60 in.)		•
Toolbox Trays		•
WINCH & WIRE ROPE		
8,000 lb. Worm Gear Winch w/ 3/8 in. x 56 ft. EIPS Galvanized Wire Rope	•	
10,000 lb. Worm Gear Winch w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope		•
12,000 lb. Worm Gear Winch w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope		•
10,000 lb. Sliding Planetary Winch w/ 7/16 in x 56 ft. EIPS Galvanized Wire Rope		•
Dual Side Manual Free Spool		•
Air Controlled Winch Free Spool		•